

APPLICATION FOR UNITED STATES LETTERS PATENT

INVENTOR(S): Kaori NAKAMURA  
Kazuyuki KOZU

INVENTION: SUBSCRIBER PROFILE CHANGING  
METHOD, SUBSCRIBER PROFILE FILE  
UPDATING METHOD, MOBILE  
COMMUNICATION SYSTEM, EXCHANGE,  
AND HOME MEMORY STATION

S P E C I F I C A T I O N

This application is based on Patent Application No. 2000-347125 filed November 14, 2000 in Japan, the content of which is incorporated hereinto by reference.

5 BACKGROUND OF THE INVENTION

FIELD OF THE INVENTION

10 The present invention relates to a subscriber profile changing method, a subscriber profile file updating method, a mobile communication system, an Exchange, and a home memory station.

15 DESCRIPTION OF THE RELATED ART

20 Fig. 1 is a diagram illustrating a communication method of downloading a subscriber profile into an exchange the service area of which contains the mobile terminal. In the example in Fig. 1, when a mobile terminal 10 becomes present in the service area of an exchange 31, it registers its location via the exchange 31. In this case, the exchange 31 downloads the subscriber profile of the mobile terminal 10 from a home memory station 20 in order to obtain information on the mobile terminal 10. The subscriber profile may be personal information, locational information, service information, or the like.

25 Figs. 2 and 3 are diagrams illustrating an example

of a process of changing a subscriber profile in prior art. When the mobile terminal 10 transmits a request to change its subscriber profile to the exchange 31 (Fig. 2(a)), the exchange 31 transmits the change request to the home memory station 20 (Fig. 2 and Fig. 3(b)). Upon receiving the change request, the home memory station 20 change the subscriber profile of the mobile terminal 10 on the basis of the request ((c)). Then, the home memory station 20 transmits a change request response to the exchange 31 ((d)). The exchange 31 transmits the received change request response to the mobile terminal 10 ((e)). Also, the home memory station 20 transmits the changed subscriber profile to the exchange 31 ((f)). The exchange 31 changes (updates) a subscriber profile of the mobile terminal 10 retained thereby to the received one ((g)). After the change, the exchange 31 responds to the home memory station 20 by notifying it that the change process has been completed at the exchange (the exchange 31) whose service area has the mobile station 10 ((h)).

With this method, the subscriber profile in the home memory station 20 is changed and then the subscriber profile in the exchange 31 is changed, so that two round trips of inter-station signals are required between the home memory station 20 and the exchange 30.

This process is used partly because if the mobile terminal 10 moves to the service area of a new exchange, the home memory station 20 must transmit its subscriber

profile to this new exchange, that is, the home memory station 20 must have the latest information.

1054735-11301  
Figs. 4 and 5 show an example of a process executed in prior art if the change of the location registration is requested after the mobile terminal has moved to the service area of a different exchange. It is assumed that the mobile terminal 10, which shifts from the service area of the exchange 31 to the service area of an exchange 32, transmits a location registration change request to the exchange 32, which is the new exchange whose service area has the mobile terminal 10. The exchange 32 transmits this location registration request to the home memory station 20 (Figs. 4 and 5(a)). Upon receiving the request, the home memory station 20 transmits a subscriber profile deletion request to the exchange 31, which is the old exchange whose service area had the mobile terminal 10 ((b)). Upon receiving the deletion request, the exchange 31 deletes its subscriber profile ((c)), and transmits a deletion completion response to the home memory station 20 ((d)). Upon receiving this response, the home memory station 20 changes its subscriber profile on the basis of the location registration request ((e)), and inputs the changed subscriber profile to the exchange 32 ((f)). Subsequently, a change process completion response is transmitted between the exchange 32 and the home memory station 20 ((g) and (h)).

Thus, in the prior art, when the subscriber profile

is to be changed, a large number of signals are transmitted and received between the home memory station and the exchange.

5

#### SUMMARY OF THE INVENTION

It is an object of the present invention to reduce the number of signals transmitted and received between the home memory station and the exchange when the subscriber profile is to be changed.

10

To accomplish the above mentioned object, in the first aspect of the present invention, there is provided a subscriber profile changing method of changing at an exchange a subscriber profile of a mobile terminal present in a service area of the exchange, the method comprising the steps of: receiving from the mobile terminal, a request to change the subscriber profile; changing the subscriber profile on the basis of the change request and retaining the changed subscriber profile; and retaining information indicating that the subscriber profile has been changed.

15

20

In the second aspect of the present invention, there is provided a subscriber profile updating method of updating a subscriber profile of a mobile terminal in a mobile communication system comprising exchanges and a home memory station, when the mobile terminal, which is present in a service area of a first exchange, moves to a service area of a second exchange, the method comprising

25

the steps of: if the subscriber profile as retained by the first exchange is changed while the mobile terminal is present in the service area of the first exchange, transmitting the subscriber profile from the first  
5 exchange to the home memory station; and updating, at the home memory station, the subscriber profile as retained thereby to the subscriber profile as received thereby; deleting, at the first exchange, the subscriber profile as retained thereby; transmitting the subscriber profile  
10 from the home memory station to the second exchange; and retaining, at the second exchange, the subscriber profile as received thereby.

In the third aspect of the present invention, there is provided a subscriber profile updating method of  
15 updating a subscriber profile of a mobile terminal in a mobile communication system comprising an exchange and a home memory station, the method comprising the steps of: if the subscriber profile as retained by the exchange is changed while the mobile terminal is present in a service  
20 area of the exchange, transmitting the subscriber profile from the exchange to the home memory station; and updating, at the home memory station, the subscriber profile as retained thereby to the subscriber profile as received thereby; and deleting, at the exchange, the subscriber  
25 profile as retained thereby.

In the fourth aspect of the present invention, there is provided an exchange comprising: means for receiving

from a mobile terminal present in a service area of the exchange, a request to change a subscriber profile of the mobile terminal; means for changing the subscriber profile on the basis of the change request and retaining the changed  
5 subscriber profile; and means for retaining information indicating that the subscriber profile has been changed.

In the fifth aspect of the present invention, there is provided a mobile communication system comprising exchanges and a home memory station, one of the exchanges  
10 comprising: means for transmitting a subscriber profile of a mobile terminal to the home memory station if the mobile terminal, which is present in a service area of the one of the exchanges, moves to a service area of another exchange and if the subscriber profile of the mobile  
15 terminal as retained by the one of the exchanges is changed while the mobile terminal is present in the service area of the one of the exchanges; means for deleting the subscriber profile of the mobile terminal as retained by the one of the exchanges if the mobile terminal, which is  
20 present in the service area of the one of the exchanges, moves to a service area of another exchange; means for receiving the subscriber profile of the mobile terminal from the home memory station if the mobile terminal, which is present in a service area of another exchange, moves  
25 to the service area of the one of the exchanges; and means for retaining the subscriber profile of the mobile terminal as received by the one of the exchange if the mobile

terminal, which is present in a service area of another exchange, moves to the service area of the one of the exchanges, and the home memory station comprising: means for receiving the subscriber profile of the mobile terminal  
5 from a first exchange if the mobile terminal, which is present in a service area of the first exchange, moves to a service area of a second exchange and if the subscriber profile of the mobile terminal as retained by the first exchange is changed while the mobile terminal is present  
10 in the service area of the first exchange; means for updating the subscriber profile as retained by the home memory station to the subscriber profile as received by the home memory station if the mobile terminal, which is present in the service area of the first exchange, moves  
15 to the service area of the second exchange and if the subscriber profile of the mobile terminal as retained by the first exchange is changed while the mobile terminal is present in the service area of the first exchange; and means for transmitting the subscriber profile of the mobile  
20 terminal to the second exchange if the mobile terminal, which is present in the service area of the first exchange, moves to the service area of the second exchange.

In the sixth aspect of the present invention, there is provided an exchange for use in a mobile communication  
25 system comprising the exchange and a home memory station, the exchange comprising: means for transmitting a subscriber profile of a mobile terminal to the home memory



10054735.11301

station if the mobile terminal, which is present in a service area of the exchange, moves to a service area of another exchange and if the subscriber profile of the mobile terminal as retained by the exchange is changed while the mobile terminal is present in the service area of the exchange; means for deleting the subscriber profile of the mobile terminal as retained by the exchange if the mobile terminal, which is present in the service area of the exchange, moves to a service area of another exchange; means for receiving the subscriber profile of the mobile terminal from the home memory station if the mobile terminal, which is present in a service area of another exchange, moves to the service area of the exchange; and means for retaining the subscriber profile of the mobile terminal as received by the exchange if the mobile terminal, which is present in a service area of another exchange, moves to the service area of the exchange.

In the seventh aspect of the present invention, there is provided a home memory station for use in a mobile communication system comprising exchanges and the home memory station, the home memory station comprising: means for receiving a subscriber profile of a mobile terminal from a first exchange if the mobile terminal, which is present in a service area of the first exchange, moves to a service area of a second exchange and if the subscriber profile of the mobile terminal as retained by the first exchange is changed while the mobile terminal is present

in the service area of the first exchange; means for updating the subscriber profile as retained by the home memory station to the subscriber profile as received by the home memory station if the mobile terminal, which is present in the service area of the first exchange, moves to the service area of the second exchange and if the subscriber profile of the mobile terminal as retained by the first exchange is changed while the mobile terminal is present in the service area of the first exchange; and means for transmitting the subscriber profile of the mobile terminal to the second exchange if the mobile terminal, which is present in the service area of the first exchange, moves to the service area of the second exchange.

In the eighth aspect of the present invention, there is provided a mobile communication system comprising an exchange and a home memory station, the exchange comprising: means for transmitting a subscriber profile of a mobile terminal to the home memory station if the subscriber profile of the mobile terminal as retained by the exchange is changed while the mobile terminal is present in the service area of the exchange; and means for deleting the subscriber profile of the mobile terminal as retained by the exchange, and the home memory station comprising: means for receiving the subscriber profile of the mobile terminal from the exchange if the subscriber profile of the mobile terminal as retained by the exchange is changed while the mobile terminal is present in the

service area of the exchange; and means for updating the subscriber profile as retained by the home memory station to the subscriber profile as received by the home memory station if the subscriber profile of the mobile terminal as retained by the exchange is changed while the mobile terminal is present in the service area of the exchange.

In the ninth aspect of the present invention, there is provided a exchange for use in a mobile communication system comprising the exchange and a home memory station, the exchange comprising: means for transmitting a subscriber profile of a mobile terminal to the home memory station if the subscriber profile of the mobile terminal as retained by the exchange is changed while the mobile terminal is present in the service area of the exchange; and means for deleting the subscriber profile of the mobile terminal as retained by the exchange.

In the tenth aspect of the present invention, there is provided a home memory station for use in a mobile communication system comprising an exchange and the home memory station, the home memory station comprising: means for receiving a subscriber profile of a mobile terminal from the exchange if the subscriber profile of the mobile terminal as retained by the exchange is changed while the mobile terminal is present in the service area of the exchange; and means for updating the subscriber profile as retained by the home memory station to the subscriber profile as received by the home memory station if the

subscriber profile of the mobile terminal as retained by the exchange is changed while the mobile terminal is present in the service area of the exchange.

The above configuration can reduce the number of signals transmitted and received between the home memory station and the exchange when the subscriber profile is to be changed.

The above and other objects, effects, features and advantages of the present invention will become more apparent from the following description of embodiments thereof taken in conjunction with the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a diagram illustrating a communication method of downloading a subscriber profile into an exchange the service area of which contains the mobile terminal;

Fig. 2 is a diagram illustrating an example of a process of changing a subscriber profile in prior art;

Fig. 3 is a diagram illustrating an example of a process of changing a subscriber profile in prior art;

Fig. 4 is a diagram showing an example of a process executed in prior art if the change of a location registration is requested after a mobile terminal has moved to the service area of a different exchange;

Fig. 5 is a diagram showing an example of a process

executed in prior art if the change of the location registration is requested after the mobile terminal has moved to the service area of a different exchange;

Fig. 6 is a diagram illustrating an example of a process of changing a subscriber profile according to an embodiment of the present invention;

Fig. 7 is a diagram showing an example of a process executed according to the embodiment of the present invention if the mobile terminal has moved to the service area of a different exchange;

Fig. 8 is a diagram showing an example of a process executed according to the embodiment of the present invention if the mobile terminal has moved to the service area of a different exchange;

Fig. 9 is a diagram showing an example of a process executed to delete the subscriber profile from the exchange in response to activation by a maintainer or the like; and

Fig. 10 is a diagram showing an example of a process executed to delete the subscriber profile from the exchange in response to activation by the maintainer or the like.

#### DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

An embodiment of the present invention will be described below in detail with reference to the drawings.

Fig. 6 is a diagram illustrating an example of a process of changing a subscriber profile according to an

embodiment of the present invention. When a mobile terminal 110 transmits a request to change its subscriber profile to an exchange 131 (Fig. 6(a)), the exchange 131 changes the subscriber profile of the mobile terminal 110 on the basis of this change request and then retains the changed profile ((b)). Furthermore, the exchange 131 sets a flag (indication) representing that the subscriber profile has been changed. That is, for example, the flag is initialized to zero and is set to one if the subscriber profile is changed. This flag indicates whether or not the subscriber profile was changed while the mobile terminal 110 was present in the service area of the exchange 131. After changing the subscriber profile, the exchange 131 transmits a change process completion response to the mobile terminal 110 ((c)).

With this method, as long as the mobile terminal remains in the service area of the same exchange, no transmissions are executed between a home memory station and the exchange even if the subscriber profile is changed.

Figs. 7 and 8 are diagrams showing an example of a process executed according to the embodiment of the present invention if the mobile terminal has moved to the service area of a different exchange. When the mobile terminal 110 moves from the service area of the exchange 131 to the service area of an exchange 132 (Fig. 7(a)) and the mobile terminal 110 transmits a location registration request to the exchange 132 (Figs. 7 and 8(b)), the exchange 132

transmits the location registration request to the home memory station ((c)). Upon receiving the location registration request, the home memory station 120 requests the exchange 131, which is the old exchange whose service area had the mobile terminal 110, to delete the subscriber profile of the mobile terminal 110 ((d)). Before deleting the subscriber profile, the mobile terminal 131 checks the flag to see whether or not the subscriber profile was changed while the mobile terminal 110 was present in the service area of the exchange 131 ((e)). If the subscriber profile has been changed, the exchange 131 sets the changed subscriber profile in a deletion request response signal and transmits the signal to the home memory station 120 ((f)). The home memory station 120 updates a subscriber profile retained thereby to the received one and then retains the latter ((g)). If the subscriber profile has not been changed, the exchange 131 simply transmits a deletion request response signal to the home memory station 120. Subsequently, the home memory station 120 inputs the subscriber profile to the exchange 132, which is the new exchange whose service area has the mobile terminal 110 ((h)). The exchange 132 retains this subscriber profile.

Figs. 9 and 10 are diagrams showing an example of a process executed to delete the subscriber profile from the exchange in response to activation by a maintainer or the like. Before deleting the subscriber profile, the mobile terminal 131 checks the flag to see whether or not the

subscriber profile was changed while the mobile terminal corresponding to the subscriber profile was present in the service area of the exchange 131 (Figs. 9 and 10(a)). If the subscriber profile has been changed, the exchange 131 sets the changed subscriber profile in a deletion report signal and transmits the signal to the home memory station 120 ((b)). The home memory station 120 updates a subscriber profile retained thereby to the received one and then retains the updated subscriber profile ((c)).

In the above description, the present invention is applied to all the subscriber profiles. However, it may be applied to some of the subscriber profiles, whereas the prior art may be applied to the others. This enables services to be discriminated from each other or prioritized. For example, the prior art may be applied to data that must not be lost (for example, ForwardedToNumber) to always update it. The present invention may be applied to data that may be lost (for example, application timer) to update it only when the need arises. The information on the application timer can be provided as a default, so that even if it is lost, no serious problem generally occurs.

As described above, the present invention can reduce the number of signals transmitted and received between the home memory station and the exchange when the subscriber profile is to be changed.

The present invention has been described in detail with respect to preferred embodiments, and it will now be



apparent from the foregoing to those skilled in the art  
that changes and modifications may be made without  
departing from the invention in its broader aspects, and  
it is the intention, therefore, in the appended claims to  
5 cover all such changes and modifications as fall within  
the true spirit of the invention.